

FLUKE®

Fluke 1740 Series Three-Phase Power Quality Loggers *Memobox*

Assess power quality and conduct long-term studies with ease



Fluke. *Keeping your world up and running.™*

Fluke Corporation

P.O. Box 9090
Everett, WA USA 98206

Fluke Europe B.V.

P.O. Box 1186
5602 BD Eindhoven
The Netherlands

For more information call:

In the U.S.A. (800) 443-5853
or Fax (425) 446 -5116
In Europe/M-East/Africa
+31 (0)40 2 675 200
or Fax +31 (0)40 2 675 222
In Canada (905) 890-7600
or Fax (905) 890-6866
From other countries +1 (425) 446 -5500
or Fax +1 (425) 446 -5116

Visit us on the worldwide web at:

www.fluke.com

Fluke (UK) Ltd.

52 Hurricane Way
Norwich
Norfolk
NR6 6JB
United Kingdom
Tel.: (020) 7942 0700
Fax: (020) 7942 0701
E-mail: industrial@uk.fluke.nl

Visit us on the worldwide web at:

www.fluke.co.uk

© Copyright 2006, Fluke Corporation. All rights reserved.
Printed in the Netherlands 06/06
Data subject to alteration without notice.

Pub_ID: 11135-eng

Fluke 1740 Series Three-Phase Power Quality Loggers Memobox

FLUKE®



Fluke 1743

Fluke 1744



Fluke 1745



The included PQ Log software helps you to quickly identify the root cause of a disturbance.



Ordering Information

Fluke 1743 Power Quality Logger Memobox
Fluke 1744 Power Quality Logger Memobox
Fluke 1745 Power Quality Logger Memobox

Includes: 4 Flexible probes 15/150/1500/3000 A with 2 m cable, CD-ROM with PQ Log software, RS232 interface cable and RS232-USB adapter, 4 black dolphin clips, Test leads for voltages and power supply, Color localization kit, Carrying bag, Test certificate with measurement values, Printed English manual, and Multi-language manual CD.

Assess power quality and conduct long-term studies with ease

Compact, rugged and reliable, the Fluke 1740 Series three-phase power quality loggers are everyday instruments for technicians who troubleshoot and analyze power distribution systems. Capable of simultaneously logging up to 500 parameters for up to 85 days and capturing events, the Fluke 1740 Series helps uncover intermittent and hard-to-find power quality issues. There are three models to choose from to meet your basic or advanced power logging needs.

- **Plug and play:** Setup in minutes with automatic current probe detection and powering
- **Installs inside the cabinet:** Compact, fully-insulated housing and accessories fit easily in tight spaces next to live power
- **Monitors power for the long-term:** Data can be downloaded during recording without interruption
- **Measure voltage with premium accuracy:** IEC61000-4-30 Class-A compliant voltage accuracy (0.1%)
- **Quickly validate quality of power:** Assess power quality according to EN50160 power quality standard with statistical overview

Specifications

(Check the Fluke web for detailed specifications)

	1745	1744	1743
Measurement of common power parameters: V, A, W, VA, VAR, PF, energy, flicker, voltage events (dips, swells, interruptions), and THD	•	•	•
Measurement of voltage and current harmonics to the 50th, unbalance, frequency and mains signaling	•	•	
Dust/water resistance	IP 50	IP 65 water proof	
Display	LED + LCD	LED	LED
Memory	8 MB	8 MB	8 MB
UPS ride-through	> 5 hrs	3s	3s
EN 50160	•	•	•

Power supply: 88 V ... 660 V ac
Safety: IEC/EN 61010-1 600 V CAT III, 300 V CAT IV, pollution degree 2, double insulation
Housing: Fully insulated housing and accessories
Operating temperature: 0 °C to 35°C
Interface: RS 232, 9600 ... 115 000 Baud, automatic Baud rate selection, 3-wire communication

Size: Fluke 1745: 282 mm x 216 mm x 74 mm;
Fluke 1743/44: 170 mm x 125 mm x 55 mm
Weight: Fluke 1745 – approx. 3 kg;
Fluke 1743/44: approx. 2 kg
Two Year Warranty

Recommended Accessories

Model	Description
• MBX CLAMP 1 A / 10 A	3-phase current clamps with 2 ranges 1 A/10 A, 2 m cable
• MBX CLAMP 5 A / 50 A + N	3-phase+N current clamps with 2 ranges 5 A/50 A, 2m cable
• MBX CLAMP 20 A / 200 A + N	3-phase+N current clamps with 2 ranges 20 A/200 A, 2 m cable
• MBX 300 POLESET	Pole mounting kit